

## **WALKER CADDY**

**NOTE:** These instructions are prepared to use upholstery/home decorator fabric which is heavier than 100% cotton. If you would like to use lighter fabric, it is recommended that batting and/or interfacing be added.

- 1. Both pieces should be approximately 15 inches wide and one is likely longer than the other. Trim so they both measure the same length. Place them right sides together and sew around perimeter using a ½ inch seam—be sure to leave an opening on one of the short sides at least 6 inches for turning.**
- 2. Clip corners to reduce bulk (no need to trim seams) and turn right side out. Poke out corners and press sides. Topstitch ends on the short side only close to the edge which will close the opening you left for turning.**
- 3. Fold the rectangle in half to find the center and mark with a pin.**
- 4. To form pockets, fold up each side toward the center leaving approximately 12 inches in between the pockets and pin on the sides.**
- 5. Stitch the pockets on each side using a ¼ inch seam. If you would like to have divided pockets, find the center of the finished width (probably about 14.5") and stitch from the top of the pocket to the bottom on each side of the caddy.**
- 6. Top stitch the center portion (the part without pockets) using a ¼ inch seam. This will give some stability to the caddy.**
- 7. To secure the caddy over the walker bar, stitch hook and loop tape (Velcro) on the center section (that does not have pockets). Place the tape along the seam and topstitch around each piece of the tape (for a total of 4) making sure the hook sides will match up with the loop sides. It may be helpful to hang the caddy over a towel bar so your hands are free to mark placement of the hook and loop tape.**

**THANK YOU FOR YOUR HELP!!!!**

**WE HOPE YOU ENJOYED THIS PROJECT**